

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
6 May 2004 (06.05.2004)

PCT

(10) International Publication Number
WO 2004/037348 A1

(51) International Patent Classification⁷: **A62B 1/10**

(21) International Application Number:
PCT/AU2003/001132

(22) International Filing Date:
3 September 2003 (03.09.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2002952251 25 October 2002 (25.10.2002) AU

(71) Applicant and
(72) Inventor: LEE, Terry, Victor [AU/AU]; 2/9 - 11 Ewos
Parade, Cronulla, New South Wales 2230 (AU).

(74) Agent: LESICAR PERRIN; 49 Wright Street, Adelaide,
South Australia 5000 (AU).


(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:
— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: ESCAPE DEVICE



(57) **Abstract:** An escape device (10) including a cable (18), a rotatable cable dispensing assembly (22) from which the cable (18) is dispensed under load, a braking mechanism (28) operatively connected to the rotatable cable dispensing assembly (22), whereby a braking response of the braking mechanism (18) is proportional to the rate at which cable (18) is dispensed from the rotatable cable dispensing assembly (22).

WO 2004/037348 A1